

7 Kayleigh Drive, Maroochydore Qld 4558 Phone: 07 5443 2111

20 Rene Street, Noosaville, Qld 4566 Phone: 07 5449 7855

134 Bulcock Street, Caloundra, Qld 4551 Phone: 07 5438 1588

QBCC License No: 69021 QBuild Registration No: 878105



Features & Benefits

• Employing Lo-Chlor Scale Defence as part of a swimming pool maintenance.

The program will reduce scale formation as well as remove existing scaling.

- Scale Defence will also will help prevent rust discolouration and staining, scum formation and plugging of filters.
- It will assist in preventing corrosion of metal parts in the recirculation and filtration system.
- Lo-Chlor Scale Defence should be added at the start of the swimming season or when a new / renovated pool is first filled.
- Periodic additions should be made throughout the entire season,
 and a final treatment should be made when the pool is "winterised"
 or is to be idle for a long period of time.

Initial Dosage:

- Add 5L of Lo-Chlor Scale Defence for every 50,000L pool water
- Add directly to the pool
- Broadcast over as great an area as possible

Monthly Maintenance:

- Add 1L of Lo-Chlor Scale Defence for every 50,000L pool water
- Broadcast over as great an area as possible

A few facts from the professionals..

- If Calcium Hardness level is above 500 ppm we recommend you treat this first either by dilution or using **Lo-Chlor Calcium Hardness Reducer**.
- After the "Initial Dose" apply product to the pool on a monthly basis to ensure constant stain and scale protection all year round.
- To remove scale discoloration on waterline tiles raise water level above the line and maintain for at least 3 weeks.



