

7 Kayleigh Drive, Maroochydore Qld 4558 Phone: 07 5443 2111

20 Rene Street, Noosaville, Qld 4566 Phone: 07 5449 7855

134 Bulcock Street, Caloundra, Qld 4551 Phone: 07 5438 1588

QBCC License No: 69021 QBuild Registration No: 878105

Lo-Chlor Stain & Scale Attack Part 1

Lo-Chlor Stain & Scale Attack Part 2

A two part pack which attacks calcium scale in swimming pools

Two highly concentrated formulations from **Lo-Chlor Chemicals** which combine to form a concentrated compound of organic acids and chelating agents in the fight against

Calcium Scale in swimming pools.

Features & Benefits

- Concentrated calcium scale remover
- Can also be used as an effective copper stain remover
- Lo-Chlor Scale Attack works best at pH 7.0.
- Make sure the Chlorine level is below 1.0 p.p.m.
- High chlorine levels will neutralise Scale Attack
- Lo-Chlor Scale Attack works very slowly. Advise the pool

owner it will take up to 6 weeks before results are sometimes seen

- Run pump, filter and Chlorinator, as normal
- Do not sprinkle onto pool surface.
- Must ALWAYS be mixed in a bucket of water first

Sizes

- 2 x 1KG Pack
- Treats up to 50,000Litres water

Dosage

- Add 1KG Scale Attack Part I to bucket of water and mix until dissolved
- Then add 1Kg Scale Attack Part II to the same solution
- Once mixed thoroughly pour around perimeter of pool

A few facts from the professionals...

- 1. After the solution is mixed thoroughly try to pour over as great an area as possible.
- 2. Immediately after the addition of Scale Attack the pool will go cloudy.
- 3. This cloudiness should disappear within 5-10 minutes
- 4. Allow to filter for at least 24 hours after application.
- 5. Rebalance the pool after 5-7 days.
- 6. Allow at least 4-6 weeks before you can expect to see any results.
- 7. To prevent the build up of new calcium scale in swimming pools add **Lo-Chlor Scale Defence** at a rate of **5LT per 50,000Litres**



